



ATLANTIC ATF - D VI

Full Synthetic ATF

PRODUCT DATA

DESCRIPTION

ATLANTIC ATF D VI is formulated with premium synthetic base stocks and advanced additive technology, and meets all the stringent requirements of General Motors' DEXRON®-VI specification, which is designed for the modern automatic transmissions in GM vehicles. **ATLANTIC ATF D VI** can be used in new and old GM automatic transmissions & it is fully back-serviceable and can be used wherever DEXRON®-II and/or DEXRON®-III are recommended.

APPLICATIONS

ATLANTIC ATF D VI is high quality ATF suitable for use in automatic transmissions with torque converters of passenger cars, as well as in wet clutches and power steering units.

PRODUCT BENEFITS

- Optimized frictional properties that provide smooth gear shifting during low temperature operation and help prevent transmission vibration
- Extends transmission fluid life and prevents fluid breakdown at higher operating temperatures
- Improved oxidation and thermal stability
- Reduces sludge and varnish build-up
- Outstanding low temperature performance
- Maintains lubricity
- Thoroughly field tested
- Low viscosity formulation provides fuel economy benefits compared with fluids formulated to meet DEXRON®IIIH or earlier specifications.
- Improved anti-wear protection which contributes to extended transmission life
- Protects transmission gears and allows them to operate smoothly

RECOMMENDATIONS / SPECIFICATIONS

Meets or Exceeds General Motors DEXRON®-VI Requirements & for 2006 and newer GM vehicles.
Meets the performance requirements of MB 236.41, Allison C-4 & VOITH H55.6335xx.

| TYPICAL TECHNICAL PROPERTIES | |
|---|---------|
| Product code | 12714AT |
| Color, VISUAL | RED |
| Density at 15°C, g/ml, ASTM D4052 | 0.847 |
| Kinematic Viscosity at 40°C, mm ² /s, ASTM D445 | 30.2 |
| Kinematic Viscosity at 100°C, mm ² /s, ASTM D445 | 6.1 |
| Viscosity Index, ASTM D2270 | 148 |
| Flash Point(COC), °C, ASTM D92 | 208 |
| Pour Point, °C, ASTM D97 | -54 |
| Brookfield viscosity at -40°C, mPa.s, ASTM D2983 | 11,000 |

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.



Packing :1USQ | 1L | 4L | 208L

ATL/PDS/ATF/005/0*, 10.08.15, Page 1/1
* supersedes all previous versions

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.