



ATLANTIC FRENO BRAKE FLUID

High Performance Glycol Ether Based Brake Fluid

PRODUCT DATA

DESCRIPTION

ATLANTIC FRENO Brake Fluids are premium quality, non-silicone, non-mineral/petroleum based, fully synthetic brake fluid designed for use in a wide range of brake and clutch applications. It offers superior dry and wet boiling points and maintains viscosity in cold and hot environments.

APPLICATIONS

Recommended for re-fill or top-up of brake and clutch systems in passenger cars, 4WD's, motorcycles, light and heavy duty commercial vehicles, mining, construction and agricultural equipment that require a non-petroleum based brake & clutch hydraulic fluid.

DOT 5.1 Suitable for use where the vehicle manufacturer specifies either DOT 3, DOT 4, or DOT 5.1 fluids.

It is also suitable for use with all types of seals, hoses and other brake and clutch system parts. Low viscosity (at -40C), for faster fluid circulation in micro-valves of ABS systems

DOT 4 Suitable for use where the vehicle manufacturer specifies DOT 3 or DOT 4 brake fluid. Better performance for life of fluid compared to DOT 3 fluids.

DOT 3 Suitable for use where the vehicle manufacturer specifies DOT 3 brake fluid.

NOTE: Intermixing of brake fluids of different grades is not recommended. Intermixing may impact braking performance of some brake systems. This product is not miscible with silicone based brake fluids. This product is not compatible with any mineral or synthetic oil based fluids

PERFORMANCE FEATURES AND BENEFITS

- Excellent braking response due to high boiling point of fluid.
- High wet boiling point ensures long term retention of fluid performance.
- Better performance for life of fluid.
- Compatible with all common brake system materials
- Borate esters to scavenge water and maintain ERBP as the fluid ages
- Anti-corrosion properties: complete brake system protection.
- Elastomer compatibility: no leakage or fluid losses.

INDUSTRY SPECIFICATIONS:

DOT 5.1 - FMVSS 116 DOT 5.1, DOT 4 and DOT 3, SAE J1703/ J1704, ISO 4925 (Class 5.1, 4 & 3)


DOT 4 - FMVSS, No. 116, DOT 4 and DOT 3, SAE J1703/J1704, ISO 4925 Class 4&3

DOT 3 - FMVSS No 116 DOT 3, SAE J1703, ISO 4925 Class 3, AS 1960-2005 Grade 1

Meets the quality requirements of European Manufacturers

TYPICAL TECHNICAL PROPERTIES			
Product code	DOT 5.1	DOT 4	DOT 3
Product code	12520ASP	12521ASP	12522ASP
Density at 15°C, g/ml, ASTM D4052	1.069	1.040	1.031
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	810	1200	1300
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	2.16	2.6	2.4
Dry ERBP (FMVSS No. 116) S.11, °C (min.)	275	263	240
Wet ERBP (FMVSS No. 116) S.12, °C (min.)	187	165	150
pH (FMVSS No. 116) S.14	7.5	8.5	9.0
Boron	-	1.30 mass%	-
Corrosion Test @ 100°C for 120hrs	Passes test	Passes test	Passes test

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.



PACKING : 200 | 225 | 250 | 450 | 485 | 500 ML

ATL/PDS/ASP/001/0*, 10.08.15, Page 1/1
* supersedes all previous versions

Health and Safety: Avoid contact with skin, varnish & paint. If skin contact occurs wash with water.