



## ATLANTIC HEAT TRANSFER FLUIDS

### High Performance Heat Transfer Fluids

#### PRODUCT DATA

##### DESCRIPTION

**ATLANTIC HEAT TRANSFER FLUIDS** are high performance HTOs formulated from highly refined base stocks that are resistant to thermal cracking and chemical oxidation & are intended for use in closed indirect heating installations. The flash points of these oils will not decrease significantly in service because of their resistance to thermal cracking at the operating temperatures for which they are recommended.

##### APPLICATIONS

**ATLANTIC HEAT TRANSFER FLUIDS** are recommended for use in open and closed installations where the bulk oil temperature ranges are as outlined in the table below and where minimum shutdown temperatures are not below -7°C.

- Bulk Oil Temperature Ranges for ATLANTIC HTO 22: Closed Systems (-7° C to 285° C), Open Systems (-7°C to 150 °C)
- Bulk Oil Temperature Ranges for ATLANTIC HTO 32: Closed Systems (-7°C to 315 °C), Open Systems (-7°C to 180 °C)
- Closed, cold-oil sealed, indirect heating and cooling systems in all kinds of industrial processes operating at bulk oil temperatures up to the maximum temperatures quoted in the table above and at atmospheric pressure.
- Open systems provided the bulk temperatures do not exceed the maximum temperatures quoted in the table above.

##### PROPERTIES

**ATLANTIC HEAT TRANSFER FLUIDS** are thermally stable and are capable of an extremely long service life without deposit formation or viscosity increase. They demonstrate specific heats and thermal conductivities that provide more rapid heat dissipation. They have good heat transfer efficiency and their viscosities are such that they can be pumped readily at both start-up and operating temperatures.

##### RECOMMENDATIONS / SPECIFICATIONS

**Meets or exceeds the requirements of:** FDA 21 CFR 178.3570, DIN 51522 (1998 - 11), NSF H1, NSF HT1


Classified as ISO 6743-12 Family Q

##### PRODUCT BENEFITS

- Performance and reliability, even in severe applications.
- High resistance to thermal cracking and decomposition
- Excellent thermal properties
- Good thermal and oxidative stability
- Improves operating efficiency of heat transfer system
- Maintains viscosity and film thickness at high temperatures to help protect equipment
- Freedom from sludge and coke deposits
- Good low temperature fluidity
- Product integrity assurance through independent verification.

TYPICAL TECHNICAL PROPERTIES		
ATLANTIC HTO	22	32
Product code	12570IL	12571IL
Density at 15°C, g/ml, ASTM D4052	0.843	0.857
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s, ASTM D445	20.2	29
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s, ASTM D445	4.2	5.1
Flash Point(COC), °C, ASTM D92	190	220
Pour Point, °C, ASTM D97	-6	-6
Micro-carbon Residue, (Conradson), wt %, ASTM D4530(max)	0.05	0.05
Copper Strip Corrosion, 3 hrs @ 100° C, ASTM D 1301A	1A	1A

**Note:** These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.



**Packing : 1 | 4 | 5 | 20 | 25 | 208L**

ATL/PDS/IL/004/0\*, 10.08.15, Page 1/1  
\* supersedes all previous versions

**Health and Safety:** This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.