



ATLANTIC MAX POWER

Premium Quality Multigrade oil

PRODUCT DATA

DESCRIPTION

Atlantic Max Power Engine Oils are premium quality engine oil developed to the highest standards of lubricant quality, reliability and dependable protection.

APPLICATIONS

Atlantic Max Power Engine Oils are suitable for a variety of automobiles, modern, high-output, multivalve, turbocharged & supercharged Gasoline powered passenger cars and Diesel powered light duty vehicles. These superior grade, highly shear-stable, multi-grade gasoline engine oils are formulated for passenger cars and light truck engines requiring optimum performance under all operating conditions.

PROPERTIES

Atlantic Max Power Engine Oils are specially formulated with high viscosity index mineral oil utilizing latest additive technology, shear stable polymer and efficient detergent additive package to provide reliable engine protection under extremely severe operating condition. This oil is also approved by leading car manufactures and meets the latest industry standards for service fill use.

PERFORMANCE FEATURES AND BENEFITS

- Excellent oxidation stability to reduce engine deposits and sludge build-up to keep engines running reliably
- Enhanced low temperature capabilities for flawless cold weather starting
- Excellent engine cleanliness and lower combustion residues.
- Excellent high and low temperature properties to provide dependable protection across a wide range of driving conditions
- Good protection against rust and corrosion
- Superior dispersants provide excellent control over soot induced oil thickening.

RECOMMENDATIONS / SPECIFICATIONS

INTERNATIONAL STANDARDS : API SN, SM, SL
ACEA: A3/B3

RECOMMENDED FOR USE: Ford, GM, PSA, BMW, VW, Audi and Mercedes-Benz

TYPICAL TECHNICAL PROPERTIES			
Viscosity Grade, SAE J300	10W-40	20W-50	20W-60
Product code	12404AL	12405AL	12406AL
Density at 15°C, g/ml, ASTM D4052	0.887	0.893	0.893
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	6860 @-25°C	8500 @-15°C	8800@-15°C
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	102.45	183.66	229
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	14.4	20.64	24.2
Viscosity Index, ASTM D2270	145	132	132
Flash Point(COC), °C, ASTM D92	222	236	240
Pour Point, °C, ASTM D97	-30	-24	-24

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.



Packing : 1L | 4L | 5L | 208L |

ATL/PDS/AL/006/0*, 10.08.15, Page 1/1
* supersedes all previous versions

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.