



ATLANTIC PREMIUM PLUS 2-CYCLE OUTBOARD OIL

Superior Performance Two-Stroke Outboard Engine Oil

PRODUCT DATA

DESCRIPTION

ATLANTIC PREMIUM PLUS 2-CYCLE OUTBOARD OIL is a high performance, two-stroke engine oil that is designed for many high performance, water-cooled two-stroke engines used in outboard marine applications. It offers clean engine and environmental performance. The combination of special base oils and additive guarantees long life. **ATLANTIC PREMIUM PLUS 2-CYCLE OUTBOARD OIL** can be used at up to a 1:50-fuel ratio depending on the manufacturer's recommendation.

APPLICATIONS

ATLANTIC PREMIUM PLUS 2-CYCLE OUTBOARD OIL is recommend for use in two-stroke engines manufactured by Johnson, Mercury, OMC, Evinrude, Mariner, Force, Mercruiser, Yamaha, Suzuki, Nissan and Tohatsu or where NMMA TC-W, TC-WII or TC-W3 oils are recommended. It is also suitable for use in light to moderate duty, air-cooled two-stroke engines that are used in power mowers, chain saws, leaf blowers and lawn trimmers.

PROPERTIES

ATLANTIC PREMIUM PLUS 2-CYCLE OUTBOARD OIL is formulated from high purified conventional mineral oils and an ashless dispersant additive system providing outstanding protection against exhaust port deposits, corrosion and wear. Spark plug fouling and pre-ignition are also minimized promoting flawless operation. The product is ideal for use in both modern and older two stroke engine models

PRODUCT BENEFITS

- Non-toxic to marine life
- Excellent detergent properties at high temperatures
- Protects against sludge formation
- Light burning, ashless formulation prevents pre-ignition, plug fouling and exhaust port blocking
- High thermal and oxidation stability
- Effective anti-wear and load carrying properties
- Promotes cleaner combustion and reduced deposits in combustion area
- Superior anti-seizure and anti-scuffing performance.
- Good dispersant properties
- Excellent moisture tolerance

RECOMMENDATIONS / SPECIFICATIONS

Meets or exceeds the quality requirements of API TC, NMMA TC-W3

TYPICAL TECHNICAL PROPERTIES	
Product code	12693ML
Density at 15°C, g/ml, ASTM D4052	0.873
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	52.9
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	8.45
Viscosity Index, ASTM D2270	134
Flash Point(COC), °C, ASTM D92	108
Pour Point, °C, ASTM D97	-36
Color, Visua	Blue

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.



Packing : 200 | 208 | 1000 L

ATL/PDS/ML/006/0*, 10.08.15, Page 1/1
* supersedes all previous versions

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.