



ATLANTIC GREASE

PRODUCT DATA

ATLANTIC CALCIUM SULFONATE COMPLEX GREASE

High Temperature Calcium Sulfonate Complex Grease

DESCRIPTION AND APPLICATION

ATLANTIC CALCIUM SULFONATE COMPLEX GREASE is a heavy duty extreme pressure grease, pre-eminently designed for the lubrication of industrial bearings working under high temperatures and high loads in the steel industry. It is also suitable as EP multi-purpose grease, in various other industrial applications where water is in frequent contact with the grease.

Always avoid contamination of the grease by dust and/or dirt when applying.

PRODUCT BENEFITS

- Multi-purpose
- Excellent thermal and mechanical stability
- Water resistant
- Long service life.
- High extreme pressure and anti-wear properties.
- Good pumpability.
- Extraordinary resistance to wash -off by water
- Excellent anti-oxidation and anti-corrosion properties
- No harmful substances

RECOMMENDATIONS / SPECIFICATIONS

ISO 6743-9: L-XBFBH 1/2, DIN 51 502: KP1/2R -25

Performances meet all Voith VN108 requirements for wet end and dryer part.

| TYPICAL TECHNICAL PROPERTIES | |
|---|-------------------|
| Product code | 12814G |
| Thickener Type | Calcium sulfonate |
| NLGI Classification | 1/2 |
| Texture | Smooth/tacky |
| Color, Visual | Brown |
| Dropping Point °C, ASTM D 566 | >300 |
| Worked Penetration @25°C 60 strokes, ASTM D 217 | 280 - 310 |
| Operating temperature range, °C | - 25 to 180 |
| Kinematic viscosity of the base oil at 40°C, mm ² /s, ASTM D 445 | 420 |
| Four ball weld load, kgf, ASTM D 2596 | 500 |
| Anti-rust performance SKF- EMCOR, DIN 51 802, rating | 0-0 |

ATL/PDS/G/008/0*, 10.08.15, Page 1/1

* supersedes all previous versions

ATLANTIC GEAR COMPOUND HEAVY

Non-Solvent Grease for Open Gears and Bearings

DESCRIPTION

ATLANTIC GEAR COMPOUND HEAVY is a non-solvent containing grease for the lubrication of open gears and bearings. This premium quality grease is manufactured with a high quality Lithium Hydroxystearate soap and blended with very high viscosity paraffinic base stocks. **ATLANTIC GEAR COMPOUND HEAVY** grease contains extreme pressure, antioxidant, antirust, molybdenum disulfide and graphite additives, and is polymer-fortified.

APPLICATION

- Excellent fluidity and can be easily used in centralized systems.
- Specially designed for the lubrication of open gears and plain bearings such as used in the mining, construction and sugar mill industries.
- Excellent performance in crushers, pulverizers, rotating mills, kilns, and in other similar large equipment.

| TYPICAL TECHNICAL PROPERTIES | |
|---|-----------|
| Product code | 12815G |
| Thickener Type | Lithium |
| NLGI Classification | 0 |
| Color, Visual | Dark Grey |
| Dropping Point °C, ASTM D 566 | 175 |
| Worked Penetration @25°C 60 strokes, ASTM D 217 | 370 |

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.



Packing : 200g | 250g | 400g | 500g | 1kg | 3kg | 15kg | 20kg | 45kg | 180kg

ATL/PDS/G/009/0*, 10.08.15, Page 1/1
* supersedes all previous versions

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.