

Atlantic Lithium Wheel Bearing Grease MP3

(LITHIUM GREASE -MP3)

Description

Atlantic Lithium Wheel Bearing Grease MP3 is Lithium MP Grease made from high quality mineral oil thickened with lithium soap and fortified with functional additives to impart oxidation and corrosion resistance

Applications

Atlantic Lithium Wheel Bearing Grease MP3 is recommended for multipurpose applications including high performance wheel bearing, chassis points, and water pump bearing. They are pumpable and can be dispensed by and greasing system. MP 3 Grease is recommended for all normal grease application areas.

Typical Characteristics

Test parameter	Limit
Product Code	12881G
Appearance	Homogeneous
NLGI Grade	3
Texture	Smooth & Shiny
Colour	Brown
Thickener type	Lithium
Penetration at 25°C, worked (60 x) ASTM D - 217	240
Base oil viscosity, kv at 40°C, cst, ASTM D - 445	100
Four ball weld load in kg, min, ASTM D 2596	180
4-Ball Wear, ASTM D 2266, Scar, mm	0.5
Timken OK Load, ASTM D2509, lb	15
Rust Protection, ASTM D 6138, Distilled Water	0-0
Dropping Point, °C, ASTM D 2265	>198
Oxidation Stability, 100 hr. psi loss @ 80°C, ASTM D 942	5
Copper Strip Corrosion, ASTM D 4048	0
Wheel Bearing Leakage, gm, ASTM D 4290	1.5

Note: The information contained herein is subject to change without notification. Typical Properties may vary slightly.

ATL/PDS/G/022/0*, 10-05-16, Page 1/1

* supersedes all previous versions

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may