

ATLANTIC SUPER SYNTECH SAE 0W40 API SN

(Fully synthetic motor oil)

DESCRIPTION

This is a full synthetic lubricant based on carefully selected very high-quality base oils of the latest generation, with a large field of application. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting. This will bring wear to a minimum. Because of its low viscosity, it is fuel-saving.

APPLICATIONS

All 4-stroke gasoline engines, four-valve, turbocharged, and 4-stroke diesel engines with or without turbo. This oil is not suitable for diesel particulate filters

PERFORMANCE FEATURES AND BENEFITS

Total engine protection: performance in keeping the engine clean. Fuel economy: superior fuel economy and CO2 reduction.

Cold start: excellent fluidity at low temperature.

RECOMMENDATIONS / SPECIFICATIONS

ACEA A3/B3, A3/B4, API SN, BMW LL01, Ford WSS-M2C937-A, MB approval 226.5, Renault RN0700.0710, MB Approval 229.5, Porsche A40, VW 502.00,505.00

TYPICAL TECHNICAL PROPERTIES

Viscosity Grade, SAE J300	0W-40
PRODUCTS CODE:	INF-3390-01
Density at 15°C, g/ml, ASTM D4052	0.844
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	5700@-35°C
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	80.1
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	13.8
Viscosity Index, ASTM D2270	178
Flash Point(COC), °C, ASTM D92	228
Pour Point, °C, ASTM D97	-45
Total Base Number (TBN)	10.1

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.

ATL/PDS/AL/040/01*, 08.02.24, Page 1/1
* supersedes all previous versions

