



# ATLANTIC WHITE OILS LLP

(Premium Grade Mineral Oil)

## DESCRIPTION

Atlantic White Mineral Oil Premium Grade is among the most versatile petroleum products derived from base oils. Because of their high purity, these oils must prefer where only highly refined products are suitable for specific viscosity requirements to develop exact required product, this is mainly required in plastics industry, Electric Industry, Cable Manufacturing, Automotive Floor Production, House Hold Products, Wine bottle Cork manufacturing diluent in cosmetics etc. We offer the Mineral Oil that meets your highest standards of quality needs.

## APPLICATIONS

- Textile Processing (non-staining lubrication)
- Incense & Perfume Manufacturing
- Dust suppressant for grain or animal feed
- Drip oil for deep well water pumps
- Process oil or diluent in adhesives, sealants, caulks, cosmetics, pharmaceuticals, rubber extender oils and plastics
- Smoke oil for air shows
- Petroleum Jelly Manufacturing
- Household cleaners and polishes

## PERFORMANCE FEATURES AND BENEFITS

- **Colorless, odorless and tasteless**
- **Excellent color stability**
- **Non-staining**

## TYPICAL TECHNICAL PROPERTIES

WHITE OIL GRADE	LLP-70/80	LLP-110
PRODUCTS CODE:	WHITE-FG-02.1-1	WHITE-FG-02.1-2
Density at 15.6°C, g/ml, ASTM D4052	0.84-0.865	0.845-0.865
Color, Saybolt, ASTM D156	+30	+30
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s, ASTM D445	12-16	18-24
Flash Point(COC), °C, ASTM D92, min	150	210
Pour Point, °C, ASTM D97, max	-21	-15

**Packing:** 165kg-180kg-1000L-20MT

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.

ATL/PDS/FG/02.1/0\*, 10.04.24, Page 1/1

\* supersedes all previous versions